

# 1808 ACCESS PLUS TELEPHONE ENTRY SYSTEM





talk to your guest at a front door or gate from any telephone in the home!



up to 27 resident / tenant phone numbers



hold open up to 4 hold open time zones



**modular** design makes installation and service easy

- Provides voice communication from the entry point between the resident/tenant and guest
- PC Programmable via the Internet, LAN, modem or direct connection to a PC
- Ideal for residential, multi-home, or small apartment house applications
- Small, built-in paper directory will hold up to 12 names. Directory is printed directly from the programming software
- Relay board available which allows use of an existing 26-bit wiegand device to be used with the Access Plus system
- Up to six (6) access control devices (card readers, keypads, RF controls, relay board) can be added to the Access Plus system
- Live relay control from your PC

FEATURES

### ACCESS CONTROL SOLUTIONS





# 1808 ACCESS PLUS

## ELEPHONE INTERCO


The Model 1808 Access Plus provides voice communication from the entry point via the central office telephone service for up to 27 residents/tenants, and can provide voice communication from the entry point for up to 23 residents/tenants without central office phone service by using the 1816 Access Plus telephone intercom add-on module. Ideal for small apartment and condominium complexes, gated communities, college resident halls, mixed-use buildings, and businesses.

**1816** Access Plus

**No Phone Line Intercom Expansion** 

12.25" W x 10.25" H x 4.25" D 311mm W x 260mm H x 108mm D

\*⊐KS



### 1808 Access Plus

with directory/message window 11" W x 7.5" H x 6.5" D 27.9cm W x 19cm H x 16.5cm D

#### 1808 Access Plus Specs

#### Communication

True full duplex Hands free

#### **Mounting Styles**

Surface mount only

#### Capacity

Up to 27 phone numbers plus 23 additional with 1816 AP intercom expansion

100 device codes (card, keypad, transmitter) 500 event history buffer

10 temporary access codes

Built in directory for 12 names

#### **Door/Gate Control**

Two relays allow for control of vehicular gate/ pedestrian gate

Add 6 additional entry points (RS485) using card, keypad, or proxy RF devices

#### **Programming Methods**

PC Programmable via the Internet, LAN, modem or direct connection to a PC

#### **Advanced Features**

Access Plus programming software included Relay board available which allows use of existing 26-bit wiegand devices Holiday schedule

Four (4) hold open time zones

Email notifications

Flourescent light kit

20-name directory

Heater kit - recommended when temperatures routinely fall below 10°F (-12°C)

Camera Ready: Optional B&W or Color CCTV camera\* \*may require additional CCTV equipment

#### **Operating Temp**

The DKS model 1816 AP telephone intercom system expands the capabilities of the 1808 to include facilities without active phone service, and does not require a dedicated

Central Office (C.O.) phone line to establish communication between the 1808 AP and

a resident's telephone. This system allows the resident to be in charge of their calls and can interface with up to 23 phone lines.

10°F to 145°F -12°C to 62°C Optional heater kit available for colder climates

#### **Electrical Requirements**

16 VAC, 20 VA System power (250 ma) U.L. listed power transformer provided Ringer equivalence: 0.0A Jack Type: RJIIC or W

#### Safety Standards

FCC (US) DUF6VT-12874-OT-0 DOC (CAN) 1736 4507 A Complies with UL 294 ETL Listed

#### **Shipping Weight**

Approximately 15-20 lbs (7-9 kg)

Warranty 2 year limited factory warranty

Distributed by:

NATIONAL

ASSOCIATION

#### DOORKING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A. Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com © 2010 All Rights Reserved. Product specifications may change without notice. Rev. 6/10

**C**IDA

**MEMBER:** 













Schedule un-lock / lock times

Live relay control from your PC

#### Options

"No phone line" intercom system in conjunction with the DKS 1816 AP