



1810 ACCESS PLUS TELEPHONE INTERCOM SYSTEM



flush mount



surface mount



led lit
directory display



up to 27
resident / tenant phone numbers



modular
design makes installation
and service easy



two mounts
surface and flush are available

- Provides voice communication from the entry point between the resident/tenant and guest
- PC Programmable via the Internet, LAN, modem or direct connection to a PC.
- Ideal for residential, multi-home, small gated community or apartment house applications
- Built-in lighted directory holds up to 27 names and is printed directly from the software program
- Relay board available which allows use of an existing 26-bit wiegand device to be used with the Access Plus system
- Up to six (6) access control devices (card readers, keypads, RF controls, relay board) can be added to the Access Plus system
- Live relay control from your PC

FEATURES

ACCESS CONTROL SOLUTIONS






1810 ACCESS PLUS TELEPHONE INTERCOM


The Model 1810 Access Plus provides voice communication from the entry point via the central office telephone service for up to 27 residents/tenants, and can provide voice communication from the entry point for up to 23 residents/tenants without central office phone service by using the 1816 Access Plus telephone intercom add-on module.

Ideal for small to medium apartment and condominium complexes, gated communities, college resident halls, mixed-use buildings, and businesses.




1810 Access Plus Surface

11.25" W x 13" H x 4.75" D
28.5cm W x 33cm H x 12cm D



1810 Access Plus Flush

12" W x 13.25" H x 3.25" D
30.4cm W x 33.7cm H x 8.25cm D



1816 Access Plus

12.25" W x 10.25" H x 4.25" D
311mm W x 260mm H x 108mm D

No Phone Line Intercom Expansion

The DKS model 1816 AP telephone intercom system expands the capabilities of the Access Plus to include facilities without active phone service, and does not require a dedicated Central Office (C.O.) phone line to establish communication between the 1810 AP and the resident's telephone. This system allows the resident to be in charge of their calls and can interface with up to 23 phone lines.

1810 Access Plus Specs

Communication

True full duplex
Hands free

Mounting Styles

Surface and flush mount

Capacity

Up to 27 phone numbers (23 with intercom)
100 device codes (card, keypad, transmitter)
500 event history buffer
10 temporary access codes
Built in directory for 27 names, easily printed with Access Plus software

Door/Gate Control

Two relays allow for control of vehicular gate/ pedestrian gate
Add 6 additional entry points (RS485) using card, keypad, or proxy RF devices

Programming Methods

PC Programmable via the Internet, LAN, modem or direct connection to a PC

Advanced Features

Access Plus programming software included
Relay board available which allows use of existing 26-bit wiegand devices
Holiday schedule
Four (4) hold open time zones
Schedule un-lock / lock times
Email notifications
Built-in lighted directory
Live relay control from your PC

Options

"No phone line" intercom system in conjunction with the DKS 1816 AP
Flourescent light kit
20-name directory
Heater kit - recommended when temperatures routinely fall below 10°F (-12°C)
Camera Ready:
Optional B&W or Color CCTV camera*
*may require additional CCTV equipment

Operating Temp

10°F to 145°F
-12°C to 62°C
Optional heater kit available for colder climates

Electrical Requirements

16 VAC, 20 VA System power (250 ma)
U.L. listed power transformer provided
Ringer equivalence: 0.0A Jack Type: RJ11C or W

Safety Standards

FCC (US) DUF6VT-12874-OT-0
DOC (CAN) 1736 4507 A
Complies with UL 294
ETL Listed

Shipping Weight

Approximately 15-20 lbs (7-9 kg)

Warranty

2 year limited factory warranty

Distributed by:

DOOR KING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A. Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2010 All Rights Reserved. Product specifications may change without notice. Rev. 6/10

MEMBER:

