TELEPHONE ENTRY / ACCESS CONTROL SYSTEM

EL25

EXPANDED CAPACITY. ENHANCED VERSATILITY.

The EL25 is beautifully engineered for private residences, yet powerful and adaptable enough to be used in apartment buildings, condo complexes, office parks and commercial sites.

The EL25 is capable of accepting up to 2000 totally flexible codes, making the EL25 ideal for virtually any installation. Unlike other systems, the EL25 may be purchased as a basic voice access control unit or can be ordered with optional plug-in modules to expand for radio, external keypad, or card reader control. This allows you to choose only the plug-in modules you need depending on the specifics of the job — enabling you to offer custom solutions right off the shelf without special orders.

LiftMaster®

EL25

STANDARD FEATURES

Call Waiting
Allows a person to answer a call from the gate or door while in the middle of another outside call.

Recessed, Lighted, ADA-Compliant Keypad
Illuminated keys with help button assistance to audibly announce the next key press on the keypad.

Auto Sensor Input
May be set to automatically dial the residence when a vehicle approaches the property.

Distinctive Ringing
Provides double ring on the telephone line to distinguish visitor request call.

Entry Codes
2000 Programmable codes can be time-restricted or established as one-time use only.

Holiday Programming
Up to 16 separate holidays can be defined to override the standard lock/unlock schedules.

Anti-Passback
Timed anti-passback waits for a preprogrammed period of time to elapse before the code or card can be reused. True anti-passback requires use of an exit reader before entering again.

Time Zones
Up to 62 different time zones with three segments each can be created for access/no access schedules.

Security Lockout
Locks out all users for a programmable period of time if several invalid code attempts are made. Alarm can be set to activate if the gate or door is held open or forced open.

Automatic Gate/Door Unlock Schedule
Entry points may be configured to automatically open or lock at set time periods.

Transaction Monitoring
A minimum of 4,000 transactions are stored in the unit including date, time, unit ID and transaction.

Activity Reports
Property managers have the ability to print database, system and history reports.

Remote Updates
System updates and upgrades may be made via remote computer over LAN, WAN, or a modem connection.

Completely Programmable Relays
4 assignable and programmable built-in relays.

Unique installation advantage
Hinge design lets you mount the unit on the back plate for ease of wiring and installation. Landscape or portrait mounting allows for versatility.

EXCLUSIVE FEATURES

Do Not Disturb
Assignable on a tenant-by-tenant basis, this may be programmed through a touch-tone phone or via a pre-programmed time schedule.

Call Forwarding
Allows each tenant to grant or deny access from a remote location. Feature may be set manually or time-activated to occur automatically.

OPTIONS

Plug-in Modules
Optional plug-in adaptability lets you expand the EL25 to work with many different types of controls. A two-reader Wiegand module lets you add card readers, keypads and prox readers, all with full activity tracking. An RF module with programmable Passport™ transmitters provides convenient remote access control.

Exclusive Security
An optional color CCTV camera ensures added security. A color low-lux camera compatible with DVRs is also available.

Lighted Directory
A separate lighted paper directory is also available in gray, nickel, silver or black.

SPECIFICATIONS

Power
12V AC

Colors
Nickel, silver, gray

Mounting Styles
Portrait or landscape

Shipping Weight
11 lbs.

Dimensions

Voice Access Controllers

EL25G
Gray unit
EL25N
Nickel unit
EL25S
Silver unit

System Accessories

RFMODKT3
315 MHz RF module for remote access with Passport™ transmitters
WOMODKT
Wiegand module that supports two Wiegand compatible remote access devices
ESSWOKSG
Essex Wiegand compatible keypad - single gang mount
HIDWOKPRO
HID, Wiegand compatible combination keypad and proximity reader
EL25CCAMKT
Color camera kit - 380 lines of resolution
EL25DVRCAMKT
DVR compatible low-lux color camera - 480 lines of resolution

Mounting Options

SNAPEDB
Gooseneck pedestal post (black)
PED42
42" pad mount, 2"x2" square black powdercoated pedestal
PED64
64" in-ground mount, 2"x2" square black powdercoated pedestal

1 YEAR WARRANTY

LiftMaster®

THE CHAMBERLAIN GROUP, INC.
845 Larch Avenue • Elmhurst, IL 60126
www.liftmaster.com

c UL us · IDA International Door Association · DASMA · I.C./F.C.C. Certified · BOMA International

©2011 The Chamberlain Group, Inc. Printed in U.S.A. 10/11 LMTECAEL25